





*AT FULL DIFFERENTIAL PRESSURE FOR CLEAN FLUIDS WITH PTFE SEATS;
TORQUE VALUES DO NOT INCLUDE SAFETY FACTORS



TOPWORKS



SIZE	A	øD	E	F	G	J1 (SQ.)	øK1	øK2	øL1	øL2	øM	NPT THREAD	ISO 5211	WEIGHT (lbs)	Cv	TORQUE* (in-lbf)	BODY BOLT SIZE	BODY NUT SIZE
1/4"	0.35 (9)	0.47 (12)	2.48 (63)	4.92 (125)	2.91 (74)	0.35 (9)	0.24 (6)	0.24 (6)	1.42 (36)	1.65 (42)	0.55 (14)	1/4"-18NPT	F03-F04	1.6	6	18	5/16" x 48	5/16"
3/8"	0.35 (9)	0.51 (13)	2.48 (63)	4.92 (125)	2.91 (74)	0.35 (9)	0.24 (6)	0.24 (6)	1.42 (36)	1.65 (42)	0.71 (18)	3/8"-18NPT	F03-F04	1.6	7	18	5/16" x 48	5/16"
1/2"	0.35 (9)	0.59 (15)	2.48 (63)	4.92 (125)	2.91 (74)	0.35 (9)	0.24 (6)	0.24 (6)	1.42 (36)	1.65 (42)	0.87 (22)	1/2"-14NPT	F03-F04	1.6	10	27	5/16" x 48	5/16"
3/4"	0.35 (9)	0.79 (20)	2.87 (73)	4.92 (125)	3.07 (78)	0.35 (9)	0.24 (6)	0.24 (6)	1.42 (36)	1.65 (42)	1.06 (27)	3/4"-14NPT	F03-F04	1.8	25	53	5/16" x 53	5/16"
1"	0.43 (11)	0.98 (25)	3.35 (85)	6.10 (155)	3.50 (89)	0.43 (11)	0.24 (6)	0.28 (7)	1.65 (42)	1.97 (50)	1.34 (34)	1"-11.5NPT	F04-F05	2.6	35	75	5/16" x 63	5/16"
1-1/4"	0.43 (11)	1.26 (32)	3.78 (96)	6.10 (155)	3.70 (94)	0.43 (11)	0.24 (6)	0.28 (7)	1.65 (42)	1.97 (50)	1.69 (43)	1-1/4"-11.5NPT	F04-F05	4.0	46	106	3/8" x 75	3/8"
1-1/2"	0.55 (14)	1.50 (38)	4.49 (114)	7.28 (185)	4.33 (110)	0.55 (14)	0.28 (7)	0.35 (9)	1.97 (50)	2.76 (70)	1.93 (49)	1-1/2"-11.5NPT	F05-F07	6.4	80	212	3/8" x 88	3/8"
2"	0.55 (14)	1.97 (50)	5.28 (134)	7.28 (185)	4.65 (118)	0.55 (14)	0.28 (7)	0.35 (9)	1.97 (50)	2.76 (70)	2.40 (61)	2"-11.5NPT	F05-F07	8.6	110	274	3/8" x 102	3/8"
2-1/2"	0.67 (17)	2.56 (65)	7.08 (180)	13.86 (352)	6.33 (161)	0.67 (17)	0.35 (9)	0.43 (11)	2.76 (70)	4.02 (102)	3.03 (77)	2-1/2"-8NPT	F07-F10	18.1	310	425	1/2" x 145	1/2"
3"	0.67 (17)	3.15 (80)	7.87 (200)	13.86 (352)	6.69 (170)	0.67 (17)	0.35 (9)	0.43 (11)	2.76 (70)	4.02 (102)	3.54 (90)	3" NPT	F07-F10	28.4	360	593	1/2" x 157	1/2"
4"	0.87 (22)	3.97 (100)	8.98 (228)	15.63 (397)	7.95 (202)	0.87 (22)	0.43 (11)	0.51 (13)	4.02 (102)	4.92 (125)	4.53 (115)	4" NPT	F10-F12	46.9	820	797	5/8" x 194	5/8"

PRODUCT INFORMATION:


1. END CONNECTIONS AVAILABLE IN: SCREWED ENDS (FNPT) AND SOCKET WELD ENDS
2. ANTI-STATIC DEVICE
3. BALL IS VENTED ON THE STEM SLOT AREA
4. BLOW-OUT PROOF STEM
5. SOCKET WELD ENDS INCLUDE ADDITIONAL PTFE BODY SEALS
6. ADJUSTABLE STEM SEAL GLAND
7. COMPLETE VALVE AUTOMATION

APPLICABLE STANDARDS:


1. ASME B16.34: DESIGN
2. API 598: INSPECTION AND TESTING
3. API 608: METAL BALL VALVES - FLANGED, THREADED, AND WELDING ENDS
4. ANSI B1.20.1: NPT
5. ISO 5211: MOUNTING
6. CGA G-4.1: CLEANING FOR OXYGEN SERVICE
7. USP CLASS VI: CONFIRMATION OF COMPLIANCE (PTFE MATERIAL)

ITEM NO.	DESCRIPTION	MATERIALS	QTY.
1	BODY	A351-CF8M	1
2	END	A351-CF8M	2
3	BALL	A351-CF8M	1
4	SEAT	PTFE	2
5	BODY SEAL	PTFE	2
6	STEM	A276-316	1
7	STEM O-RING	VITON	1
8	STEM THRUST WASHER	TFM4215	1
9	STEM SEAL	VITON	1
10	STEM PACKING	PTFE	3
11	GLAND FOLLOWER	304 STAINLESS STEEL	1
12	GLAND	A351-CF8	1
13	STOPPER	304 STAINLESS STEEL	1
14	SNAP RING	304 STAINLESS STEEL	1
15	LEVER HANDLE	A351-CF8	1
16	HANDLE BOLT	304 STAINLESS STEEL	1
17	HANDLE SLEEVE	PLASTIC	1
18	BOLT	304 STAINLESS STEEL	2
19	NUT	304 STAINLESS STEEL	2
20	BODY BOLT	304 STAINLESS STEEL	4
21	SPRING WASHER	304 STAINLESS STEEL	4
22	BODY NUT	304 STAINLESS STEEL	4

END CONFIGURATIONS:



SOCKET WELD END



SCREWED END

DRAWN BY E.P.	DATE 05/02/2017
CHECKED BY K.C.	DATE 09/15/2025
APPROVED BY J.S.	DATE 09/15/2025
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SVF FLOW CONTROLS, INC. ANY REPRODUCTION IN PART OR IN WHOLE WITHOUT THE WRITTEN CONSENT OF SVF FLOW CONTROLS, INC. IS PROHIBITED.	
PROJECTION THIRD ANGLE:	

SVF FLOW CONTROLS

5595 Fresca Drive • La Palma, CA 90623 • 1.800.783.7836
www.SVF.net • Sales@SVF.net

DESCRIPTION:

1/4" - 4" E29B 3-PIECE DIRECT MOUNT BALL VALVE, FULL BORE

UNITS: INCH (MILLIMETERS)

DATE: 09/15/2025

REV: F